

Multimetrix®

DMM 111 / DMM 121 / DMM 141 Digital Multimeters



- Large display
- 10 A calibre
- Double OFF position
- Protection by safety fuses
- 600V CAT III /Compliant with IEC 61010-2-033

CE

Multimetrix®

Specifications :

		DMM 111	DMM 121	DMM 141
Display		2,000 counts	4,000 counts	
Type of measurement		Average		RMS
I _{DC}	Ranges	200 µA / 2000 µA / 20 mA / 200 mA / 2 A / 10 A ⁽¹⁾	400 µA / 4000 µA / 40 mA / 400 mA / 4 A / 10 A ⁽¹⁾	
	Best accuracy	1%R + 3 cts	1%R + 3 cts	
	Best resolution	0.1 µA		
I _{AC}	Ranges	200 µA / 2000 µA / 20 mA / 200 mA / 2 A / 10 A ⁽¹⁾	400 µA / 4000 µA / 40 mA / 400 mA / 4 A / 10 A ⁽¹⁾	
	Best accuracy	1%R + 5 cts	1%R + 5 cts	
	Best resolution	0.1 µA		
V _{DC}	Ranges	200 mV / 2 V / 20 V / 200 V / 600 V	400 mV / 4 V / 40 V / 400 V / 600 V	
	Best accuracy	0.5%R + 3 cts	0.5%R + 3 cts	
	Best resolution	0.1 mV		
V _{AC}	Ranges	200 mV / 2 V / 20 V / 200 V / 600 V	400 mV / 4 V / 40 V / 400 V / 600 V	
	Best accuracy	1%R + 5 cts	1%R + 5 cts	
	Best resolution	0.1 mV		
Resistance	Ranges	200 Ω / 2 kΩ / 20 kΩ / 200 kΩ / 2 MΩ / 20 MΩ	400 Ω / 4 kΩ / 40 kΩ / 400 kΩ / 4 MΩ / 40 MΩ	
	Best accuracy	0.5%R + 2 cts	0.5%R + 2 cts	
	Best resolution	0.1 Ω		
Continuity (with buzzer)		Yes		
Diode test		Yes		
Frequency		-	5 Hz / 50 Hz / 500 Hz / 5 kHz / 50 kHz / 500 kHz / 50 MHz	
Capacitance		-	50 nF / 500 nF / 5 µF / 50 µF / 100 µF	
Range selection		Automatic / Manual ⁽²⁾		
Other features		Data Hold, deactivatable automatic power-off, MAX	Backlighting, Data Hold, deactivatable automatic power-off, Relative mode	
Safety		600 V CAT III according to IEC 61010-1, 61010-2-033		
Dimensions / Weight		181 x 92 x 57 mm / 335 g (without batteries)		

⁽¹⁾ 20 A max / 30 s max

⁽²⁾ except for frequency and capacitance

State at delivery :

- 1 set of red/black cables with test probes
- 1 shockproof protective sheath
- 2 x 1.5V AA batteries



built-in test-probe stowing system

To order :

Product name	Reference
DMM 111	P06231420Z
DMM 121	P06231421Z
DMM 141	P06231422Z

Multimetrix®

CHAUVIN ARNOUX group
 190 rue Championnet
 75876 PARIS cedex 18 - France
 Tél. : +33 (0)1 44 85 44 85
 Fax : +33 (0)1 46 27 73 89
 info@multimetrix.fr
 www.multimetrix.fr